

IMAGE DENOSING USING VISHUSHRINK ALGORITHM

MR. PRASHANT L PARMAR ,

M.E.[signal processing and VLSI technology] Student, Department Of Electronics and
Communication Engineering , Vishwakarma Government Engineering College
Chandkheda , Gandhinagar.
Prashant.parmar32@gmail.com,

ABSTRACT: Transmission of any visual information transmitted in the form of digital images is becoming a major method of communication now days, but the image obtained after transmission is often corrupted with noise. The received noisy image needs to enhance (denoising) processing before it can be used in applications. Image denoising is important task to produce a visually high quality image. Image denoising have been done so far decade by using histogram, linear, nonlinear methods and algorithms. In that they use transformation from one domain to another such as Fourier transform, Short Fourier transform, Wavelet and curvelet transform..In such domain various algorithms like Visushrink, Sureshrink Bayesshrink,

Keywords— Soft thresholding, Hard thresholding, Semisoft thresholding, Discrete Wavelet Transform (DWT).

I: INTRODUCTION

An image is often corrupted by noise during its acquisition and transmission. Image denoising is used to remove the additive Gaussian noise while retaining important maximum possible image features. Wavelet analysis has been demonstrated to be one of the powerful methods for performing image noise reduction. The procedure for noise reduction is applied on the wavelet coefficients obtained after applying the wavelet transform to the image at different scales. The motivation for using the wavelet transform is that it is good for energy compaction since the small and large coefficients are more likely due to noise and important image features, respectively. The small coefficients can be thresholded without affecting the significant features of the image. In its most basic form, each coefficient is thresholded by comparing against a value, called threshold. If the coefficient is smaller than the threshold, it is set to zero; otherwise it is kept either as it is or modified. The inverse wavelet transform on the resultant image leads to reconstruction of the image with essential characteristics.

II: MOTIVATION FOR WAVELET THRESHOLDING

The plot of wavelet coefficients suggests that small coefficients are dominated by noise, while coefficients with a large absolute value carry more signal information than noise. Replacing noisy coefficients (small coefficients below a certain threshold value) by zero and an inverse wavelet transform may lead to a reconstruction that has lesser noise. Stated more precisely, we are motivated to this thresholding idea based on the following assumptions:

1. The decorrelating property of a wavelet transform creates a sparse signal: most untouched coefficients are zero or close to zero.
2. Noise is spread out equally along all coefficients.
3. The noise level is not too high so that we can distinguish the signal wavelet coefficients from the noisy ones.

As it turns out, this method is indeed effective and thresholding is a simple and efficient method for noise reduction. Further, inserting zeros creates more sparsity in the wavelet domain and here we see a link between wavelet denoising and compression which has been described in sources such as [5].

III: HARD THRESHOLDING

All coefficients whose magnitude is greater than the selected threshold value to remain as they are and the others with magnitudes smaller than t are set to zero. It creates a region around zero where the coefficients are considered negligible. And it can be defined as

$$T_H = \begin{cases} x & \text{for } |x| \geq t \\ 0 & \text{in all other regions} \end{cases}$$

IV: SOFT THRESHOLDING

Soft thresholding is where the coefficients with greater than the threshold are Shrunken towards zero after comparing them to a threshold value. It is defined as follows

$$T_s = \begin{cases} \text{sign}(x)(|x| - t) & \text{for } |x| \geq t \\ 0 & \text{in all other regions} \end{cases}$$

V: SEMISOFT THRESHOLDING

The soft thresholding function (also called the shrinkage function) takes the argument and shrinks it toward zero by the threshold. Soft thresholding rule is chosen over hard thresholding, for the soft thresholding method yields more visually pleasant images over hard thresholding. By choosing appropriate thresholds, the semi-soft shrinkage offers advantages over both hard thresholding (uniformly small risk and less sensitivity to small perturbations in the data) and soft shrinkage (small bias and overall risk). Since the soft-thresholding functions are continuous with discontinuous derivative

$$T_{ss} = \begin{cases} 0 & |x| \leq t_1 \\ \text{sign}(x) \left(\frac{t_2|x| - t_1}{t_2 - t_1} \right) & t_1 < |x| \leq t_2 \\ x & |x| > t_2 \end{cases}$$

VI: VISUSHRINK ALGORITHM

Visushrink is thresholding by applying the Universal threshold proposed by Donoho and Johnstone. This threshold is given by $\sigma\sqrt{2\log M}$ where σ is the noise variance and M is the number of pixels in the image. For the maximum of any M values n_{ii} (noise matrix elements) as $N(0, \sigma^2)$ will be smaller than the universal threshold with high probability, with the probability approaching 1 as M increases. Thus, with high probability, a pure noise signal is estimated as being identically zero[1].

However, for denoising images, Visushrink is found to yield an overly smoothed estimate. This is because the universal threshold(UT) is derived under the constraint that with high probability the estimate should be at least as smooth as the signal. So the UT tends to be high for large values of M , killing many signal coefficients along with the noise. Thus, the threshold does not adapt well to discontinuities in the signal[1].

The threshold in VisuShrink is also referred to as universal threshold and it is defined as:

$$T = \sigma\sqrt{2\log M}$$

where σ is the noise variance present in the signal and M represents the signal size or number of samples.

An estimate of the noise level σ is defined based on the median absolute deviation that is given by:

$$\sigma^2 = \left[\frac{(\text{median } |Y_{i,j}|)}{0.6745} \right]^2$$

where $Y_{i,j} \in HH_1$ subband.

Visushrink algorithm steps as follow:

1. Convert the image in frequency domain
2. Estimate the threshold value
3. Apply the soft or hard thresholding
4. Reconstruct image form frequency domain

VII: EXPERIMENTAL RESULT

First I find the universal threshold value from the wavelet coefficient of the high frequency band then I apply soft thresholding , hard thresholding and semi soft thresholding and their experiment results are shown below



FIG 1 . Noisy image



FIG 2 . Soft thresholding



FIG 3 . Hard thresholding



FIG 4 . Semi soft thresholding

IX:CONCLUSION

From the different experiment of shrinkage function, the resultant denoised images which depends upon original images edges, if more edges than image get more blurred. The threshold value plays an important role in the whole process if high threshold value than it loses image detail wavelet coefficient and if it is lower than noisy wavelet coefficient passes. Semisoft thresholding has two threshold values and has both shrinkage function (hard and soft) advantages. For different images, results are as follows (in terms of PSNR):

	soft	hard	semisoft
cameraman	25.13	26.77	26.98
Leena	26.98	27.44	27.50
moon	29.24	29.77	30.32

REFERENCES

[1] Mohideen, S.K., A novel approach for image denoising using dynamic tracking with new threshold technique," *Computational Intelligence and Computing Research (ICCIC), 2010 IEEE International Conference on*, 28-29 Dec. 2010.

[2] Zhou, Dengwen Shen and Xiaoliu, Image Denoising Using Block Thresholding," *Image and Signal Processing, 2008. CISP '08. Congress on*, Vol. 3, No. 335- 338, 27-30 May 2008

[3] E. Hostalkova, A.Prochazka, Wavelet Signal And Image Denoising," *Institute of Chemical Technology, Prague Department of Computing and Control Engineering Technich* ", Dec. 2009.

[4] Song Yu, Zhai Shuang and Liu Meili, The Improved Wavelets Threshold Denoising

Algorithm Based on Region Correlation,"*IEEE International Conference on Computer, Mechatronics", Control and Electronic Engineering (CMCE)*, Vol. 10, No. 47-49, 2010.

[5] Andreas Wrangsj and Hans Knutsson, Histogram Filters for Noise Reduction," *Medical Informatics, Department of Biomedical Engineering, Linköping University*"

[6] S.Sudhacom, G.R.Suresh, and R.Sukanesh, Wavelet Based Image Denoising using Adaptive Thresholding, " *International Conference on Computational Intelligence and Multimedia Applications 2007*", Vol. 132, No.296-300, 2012

[7] J S Bhat, B N Jagadale and Lakshminarayan H K, Image De-noising with an Optimal Threshold using Wavelets " *International Conference on Signal and Image Processing*", No.436-439, 2010

[8] Noise Modelling and image laboratory , "Technical University Of Cluj-Napoca, Computer And Science Department" ,2008.

[9] "Insight Into Wavelets From Theory to Practice" K.P. Soman, K.I. Ramachandran, Tata McGraw Hill Publishing Company.